






DAW-K 130/20 PP DAW-K 130/20 PP1

Sound projectors the DAW 130/20 PP series, made from ABS, are ideal solution for both music and voice evacuation announcements. This series is recommended for warehouses, logistic halls, tunnels, corridors. With high IP 54 protection rate this loudspeaker is perfect solution also for humid areas and spaces where more weather resistance is required. DAW-K 130/20 PP is equipped with a 130 mm full-range 20 W speaker with 100 V transformer, includes ceramic block and the thermal fuse. Furthermore the mounting of the sound projector series is very comfortable due to the swivel-slope-technique of the U-mounting bracket. The loudspeaker is painted in standard RAL 9010, but any other RAL color is available as an option. This loudspeaker is optionally offered in PP1 version – it means instead of ceramic block and thermal fuse it is equipped just with a plastic connection block (5x2).



Model	DAW-K 130/20 PP DAW-K 130/20 PP1
Type	sound projector (ABS)
Application	ceiling/wall
Certificate Number	1438-CPR-0199
Speaker Type	130 mm full range
Rated power [W]	20
Driver impedance [Ω]	8
Impedance 100V [Ω]	500/667/1000/2000
Tappings 100V [W]	20/15/10/5
Frequency Range (-10dB) [Hz]	220-18500*
SPL 1W/1 m [dB]	91,1*
SPL Pmax/1 m [dB]	104,1*
Sensitivity 1W/4 m EN 54-24 [dB]	79,7
SPL max (rated noise power/4 m) EN 54-24 [dB]	91,3
Dispersion -6dB, 500 Hz/1 kHz/2 kHz/4kHz [°]	360/150/102,5/70
Connection PP/PP1	2x3 pole ceramic cube/ 2x5 pole connector
Temperature range [°C]	<-25, +70>
Type A/B/C	B
IP Rating according to EN 54-24 / IP Rating****	IP33C / IP54**
Dimensions [mm]	Ø137***x200
Weight [kg]	1,7
Material	ABS
Colour	RAL 9010
Packing Unit	8

* measured in institute other than BIP CNBOP - following PN-EN 60268-5:2005

** measured in institute other than BIP CNBOP *** without hanging bracket

