

## DS-1600KI(B) Network Keyboard



- High-performance, full-featured network keyboard
- Built-in Android system provides powerful control functions
- User friendly touch screen makes operation easy
- Flexible configuration via network
- Supports various cameras, NVRs and DVRs

## ▪ Specification

| Interface                   |   |
|-----------------------------|---|
| USB Interface               | 2 × USB 2.0   |
| Serial Interface            | Network, RS-232, RS-422, RS-485   |
| Network Interface           | 10/100/1000 Mbps adaptive ethernet port;<br>WiFi: Supported   |
| General                     |   |
| Working Temperature         | -10 to +55° C (14 to 131° F)  |
| Working Humidity            | 10% to 90%  |
| Net Weight                  | 1.7 kg (3.75 lb)  |
| Dimensions (W × H × D)      | 404 mm × 163 mm × 180 mm (15.91" × 6.42" × 7.09")   |
| Power Consumption           | ≤15 W   |
| Power Supply                | 12 VDC/PoE  |
| Display                     | 10.1" TFT LCD touchscreen, Resolution: 1280 × 800   |
| Joystick                    | 4-axis joystick   |
| Video                       |   |
| Video Output Interface Type | 1 × HDMI, 1 × DVI   |
| Audio Interface             | Audio Input: 1-ch, 3.5 mm connector (2.0 Vp-p, >1 KΩ)<br>Audio Output: 1-ch, 3.5 mm connector (2.0 Vp-p, 600 Ω) |
| Certification               |   |
| Obtained Certification      | CE-EMC/CE-LVD/ROHS/CB/UL/FCC-SDoC/RCM/BIS   |

## ▪ Available Model

DS-1600KI

DS-1600KI(B)

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionhq