



AIB-800

8CH AI Box



Key Features

- Max up to 8CH inputs
- AI functions
 - Classified object type: Person/Vehicle
 - Attributes: Person (Type: age, gender, color etc.)
 - Attributes: Vehicle (Type: car/bus/truck/motorcycle/bicycle)
- Support BestShot
- Analytics events based on AI engine
 - Motion detection, Object detection, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit)
 - Some of the video analytics only works with people/vehicle detection
- Analytics events
 - Virtual area (Appear/Disappear)
- Business Intelligence
 - Based on AI engine: People counting, Vehicle counting, Queue management, Heatmap
- Viewer Software: Web viewer, WAVE, SSM, Genetec, Milestone
- Support SDK/CGI(SUNAPI) for interworking with 3rd party VMS

AIB-800

8CH AI Box



Specifications

Display

Network	Inputs	Max. 8CH
	Resolution	CIF ~ 32MP
	Protocols	SUNAPI, ONVIF

Intelligent Analysis

AI function	Pre-Installed Event	Analytics events based on AI engine: Motion Detection*, Object detection, Virtual line* (Crossing/Direction), Virtual area* (Loitering/Intrusion/Enter/Exit), Analytics events : Virtual area(Appear/Disappear), * Some of the video analytics only works with people/vehicle detection, Classified object type : Person/Vehicle, Business Intelligence (Based on AI engine) : People counting, Vehicle counting, Queue management, Heatmap, Attributes : Vehicle (Type:car/bus/truck/motorcycle/bicycle), Support Bestshot
-------------	---------------------	---

Network

Protocol	ARP, RTP (UDP), ONVIF (Profile-S), DNS, RTSP, SRTP, UDP/IP, SUNAPI(Server, Client), HTTP, TCP/IP, uPnP, DDNS, NTP, DHCP (Server, Client), IGMP, HTTPS, SNMP, RTP (TCP), SMTP, ICMP	
DDNS	Hanwha DDNS	
Max Manipulated Streams	80 Streams (10 Streams per 1CH)	
IP Version	IPv4/v6	
Security	User access Log, 802.1x, IP address filtering, Encryption, Device certificate(Hanwha Vision Root CA)	
Language	Chinese, Polish, Japanese, German, Portuguese, Turkish, Spanish, Korean, Hungarian, English, Czech, Russian, Dutch, Italian, French, Greek	
OS	macOS 10.13, Windows 11/10	
Web Browser	Mac Safari, Microsoft Edge, Google Chrome	
Viewer Software	Type	Milestone, Genetec, SSM, WAVE, WebViewer
	CMS Support	Support SDK/CGI(SUNAPI) for interworking with 3rd party VMS

Functions

Camera Setup	Register	Auto, Manual
	Setup Items	Camera Webpage

Indicator/Interface

Front	Indicator	LED(Status indicator) : Alarm(1), Power(1), Network(1)
	Ethernet	RJ-45 1ea (1Gbps)
	Alarm	(1) In(8EA, Terminal Block), (3) Out(4EA, Terminal Block) - Relay Out1(NO/NC/COM) - Relay Out2~4(NO/COM), (2) Alarm Reset(1EA)
	USB	1EA(Rear 1 x USB 3.0) for DEBUG
	Serial	Not Supported (internal Debug)
	Reset	Factory Reset
	Power Cord	DIN 4P 12V, 4A

System

Log	Log List	Max. 3,000 (System 1,000, Access 1,000, EVENT 1,000)
CPU		NVIDIA ORIN NX 8GB (SOM)

Environmental

Operating Temperature / Humidity	+0°C to +40°C(+32°F to +104°F)
Humidity	20% ~ 85% RH

Electrical

Power	100~240 VAC \pm 10%; 50/60Hz, 12V, 4A Adaptor
Power Consumption	28W

Mechanical

Color / Material	Black / Metal
Dimension (WxHxD)	300x47.6x240.9mm(11.81x1.87x9.48inch)
Weight	1.39kg

AIB-800

8CH AI Box



CAD

Unit: mm [inch]

