



# SPA-B1000

## IP Audio Bridge



### Key Features

- Maximum Input Level: L, R : +6dBV Max
- Power: PoE (IEEE 802.3 af type 1 Class 0), DC 24V
- Internal Memory: 1 GBytes
- External Memory (Micro SD): SDHC upto 32GB (SANDISK)
- Supported Protocol: IPv4, HTTP, HTTPS, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
- Supported Supported Audio Format: WAV, MP3 in mono/stereo from 64 kbps to 320 kbps (File Streaming). Sampling rate from 16 kHz up to 48 kHz

# SPA-B1000

IP Audio Bridge



## Specifications

<b>Product</b>	
Type	IP Audio Bridge
<b>Line Input</b>	
Maximum Input Level	L, R : +6dBV Max
<b>Network</b>	
Ethernet	10/100 Base-T
<b>Memory</b>	
Internal Memory	1 GBytes
External Memory (Micro SD)	SDHC upto 32GB (SANDISK)
<b>Contact</b>	
Contact Input. Dry contact	One channel
Contact Output. Dry contact (NO)	One channel
<b>General</b>	
Operating Temperature	-20 ~ +50°C (-4°F ~ +122°F)
Operating Humidity	10~95% RH (Non-Condensing)
Weight	0.24 Kg
Size	123(W)*80(H)*30.6(D)mm
Color	White
Certificate	EMC : KS C 9832/9835, EN 55032/55035, FCC Part 15 Subpart B, ICES-003 Safety : KC 62368-1, UL 62368-1, CAN/CSA 62368-1
<b>Power</b>	
PoE	PoE (IEEE 802.3 af type 1 Class 0), DC 24V
<b>Audio</b>	
Supported Audio Format	File Streaming: WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Sampling rate from 16 kHz up to 48 kHz
<b>Network Protocol</b>	
Security	Password protection : admin,setup,user,guest (sha-2, Digest authentication, User access log) Digest authentication, User access log
Supported Protocols	IPv4, HTTP, HTTPS, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
<b>System Integration</b>	

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com).  
Hanwha Vision is formerly known as Hanwha Techwin.

API (Application Programming Interface)	SUNAPI
Event & Preset	Virtual Contact, Dry contact
Functional Monitoring	Connection verification, Built-in system logging

# SPA-B1000

IP Audio Bridge



CAD

Unit:mm [inch]

