

CODE: **HDMI-VGA** v.1.0/1  
 TYPE: **HDMI-VGA signal converter**

EN\*\*



## DESCRIPTION

The HDMI-VGA signal converter allows connecting devices (DVRs/NVRs) equipped with HDMI sockets to monitors using only a VGA (D-Sub) input. The device requires power, which is supplied directly from the DVR's USB port (the cable is attached to the converter).

In addition to the image, the converter also allows sending audio to an external source (e.g. active speakers, audio amplifier). For this purpose, the 3.5 "mm jack is used.

## TECHNICAL DATA

Code	HDMI-VGA
<b>Video output</b>	1 x HDMI (outlet) (HDMI 1,3) (HDCP 1,4)
<b>Video output / supported resolutions</b>	1 x VGA 640x480@60/72/75/85Hz; 800x600@60/72/75/85Hz 1024x768@60/70/75/85Hz; 1152x864@75Hz; 1280x720@60Hz 1280x768@60Hz; 1280x800@60Hz 1280x960@60Hz; 1280x1024@60Hz 1360x768@60Hz; 1440x1050@60Hz 1440x900@60Hz; 1680x1050@60Hz 1600x1200@60Hz; 1920x1080@60Hz
<b>Audio output</b>	1 x 3,5mm Jack (outlet)
<b>Power input</b>	1 x USB (mini) (outlet)
<b>Operation temperature</b>	-10°C ÷ 40°C
<b>Storage temperature</b>	-20°C ÷ 60°C
<b>Attenuation</b>	0,05dB
<b>Permissible relative humidity</b>	relative humidity 5÷90% without condensation
<b>Dimensions</b>	66 × 55 × 20mm
<b>Net / gross weight</b>	0,05 / 0,07kg
<b>Declarations, warranty</b>	CE, one year from the production date



### WEEE MARK

According to the EU WEE Directive – It is required not to dispose of electric or electronic waste as unsorted municipal waste and to collect such WEEE separately.