




## WAC 165/6 PP1

WAC 165/6 PP1 is a choice of designers and architects - this is an elegant, rectangular loudspeaker with a modern rounded shape, made of ABS. It is used wherever the appearance of an interior is important. Banquet halls, restaurants, conference centres, museums, shops, but also hotels and offices are ideal spaces for this loudspeaker. It can be mounted on a wall either vertically or horizontally. It is equipped with a high quality 130 mm full-range speaker and 100V transformer. The connection unit has a ceramic terminal block with thermal fuse. The loudspeaker has IP 32 rating. The housing and loudspeaker's grille are painted in RAL 9010.







Model	WAC 165/6 PP1
Туре	wall ABS
Application	wall
Certificate Number	1438/CPD/0201
Speaker Type	165 mm full-range
Rated power [W]	6
Driver impedance [ $\Omega$ ]	8
Impedance 100V [Ω]	1667/3333/6667/13333
Tappings 100V [W]	6/3/1,5/0,75
Frequency Range (-10dB) [Hz]	145-19000*
SPL 1W/1 m [dB]	96**
SPL Pmax/1 m [dB]	101*
Sensitivity 1W/4 m EN 54-24 [dB]	84
SPL max (rated noise power/4 m) EN 54-24 [dB]	96,1
Dispersion -6dB, 500 Hz/1 kHz/2 kHz/4kHz [°]	180/170/125/60
Connection PP/PP1	2x3 pole ceramic block
Temperature range [°C]	<-10, +55>
Type A/B/C	A
IP Rating according to EN 54-24 / IP Rating	21C/32**
Dimensions [mm]	330x209x84
Weight [kg]	1,2
Material	ABS
Colour	RAL 9010
Packing Unit	12

<sup>\*</sup> meassured in institiute other than BIP CNBOP - following PN-EN 60268-5:2005

www.partneraudio.eu



<sup>\*\*</sup>parameter calculated \*\*\*tested in institute other than BIP-CNBOP