



PoE injector compliant with industry standards

60W Single Port Power over Ethernet

Gigabit support Over-voltage/current protection functions

Key Features

1. Compliant with industry standards

- IEEE802.3bt/at/af

2.PoE power supply capabilities up to 60W with RJ45 models

3.Installation improvement

- A single cable to supply power and data. 100 to 240 V electrical installation qualifications is not required.

Key i-PRO Spec.

- Compliant with IEEE802.3bt Standard
- Limited Power Source
- Compliant with Phihong Proprietary 12.5K Detection
- Single Source 4 Pair Power Current Sharing
- Non-Vented Case
- Broken Wire Detection
- 4 Pair Powering +3,6,4,5 / 1,2,7,8
- Gigabit Compatible
- Full Protection OVP, OCP




Specifications

General	Safety	UL (UL62368-1), c-UL (CSA C22.2 No.62368-1), CE, IEC62368-1
	Power source	100 to 240 V AC (50 Hz/60 Hz)
	AC Input Current	2.0 A (RMS) max for 90 V AC
		1.2 A (RMS) max for 240 V AC
	Output power consumption	56 V DC: Approx. 1.07A / 60 W
		(Combined output on data pairs and spare pairs.)
	Ambient operating temperature	60 W output: -10 °C to +40 °C {14 °F to 104 °F}
		30 W output: -10 °C to +50 °C {14 °F to 122 °F}
	Ambient operating humidity	10 % to 90 % (no condensation)
	Storage temperature	-20 °C to +65 °C {-4 °F to +149 °F}
	Storage humidity	10 % to 90 % (no condensation)
	Dimension	65 mm (W) × 36 mm (H) × 163 mm (D) {2-9/16 inches (W) × 1-13/32 inches (H) × 6-13/32 inches (D)} (excluding cord and plug)
	Mass	Approx. 300 g {0.66 lbs}
	Finish	PC/ABS resin, Matte black
Network	Network I/F	10BASE-T/100BASE-TX/1000BASE-T, RJ45 connector (×2)
		Compliant with IEEE802.3bt/at/af Standard
Indicator	LED Indicator	LED indicator (×1)
Standard Accessories		Operating Instructions
		Power cord (C type) (BF type) each 1 pc.

Appearance

Unit : mm (inches)



Trademarks and registered trademarks

- All other trademarks identified herein are the property of their respective owners.

Important

- Safety Precautions : Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or other manufacturers' products used on the network.
- Masses and dimensions are approximate.
 Specifications are subject to change without notice.



i-PRO Co., Ltd. https://i-pro.com/ (2A-359BA)