

New U-series compact network camera with enhanced functions and affordability

4MP Varifocal Lens Indoor Dome Network Camera

The new U series is an entry model that achieves high quality and reliability at an affordable price to meet the needs of a wide range of customers. The compact and slim design allows it to be installed in a various locations.

It newly supports ONVIF G / S / T profile and H.265 / H.264, and can be widely used for connecting various VMS and recorders. It also comes pre-installed with secure certificates, enabling device authentication and end-to-end communication encryption to counter the threat of advanced cyberattacks.

Key features

- Compact and slim design allows installation in various locations
- Compliant with ONVIF G / S / T profile and H.265 / H.264, and can support a wide range of connections to VMS and recorders
- Uses "Easy Kitting Packing" that allows you to set the camera without removing it from the box
- Strengthen cyber security by pre-installing digital certificates issued by a third party organization (GlobalSign)

Key i-PRO Spec.

- 5MP Sensor
- 2688×1520 pixel image up to 30fps
- 2.5x built-in motorized zoom and motorized focus lens
- iA (intelligent Auto)
- Super Dynamic 102dB
- Color night vision (0.019 to 0.3 lx)
- H.265 Smart Coding
- Corridor mode
(90 degrees or 270 degrees in image rotation)
- Built-in IR LED
- ONVIF® Profile G / S / T
*ONVIF is a trademark of ONVIF, Inc.
- Genetec Stratocast compatible

Industry examples

- Retail
- Education
- Public safety
- Bank / Hospital / Building



Specifications

| | | | | | |
|---------------------------|---|---|---------------------------------------|--|--|
| Camera | Image Sensor | Approx. 1/2.7 type CMOS image sensor | | | |
| | Minimum Illumination | Color : 0.3 lx, BW : 0.12 lx (50IRE, F2.0, Maximum shutter : Off (1/30s), AGC : 11) BW : 0 lx (50IRE, F2.0, Maximum shutter : Off (1/30 s), AGC : 11, when the IR LED is lit) Color : 0.019 lx, BW : 0.0075 lx (50IRE, F2.0, Maximum shutter : max. 16/30s, AGC : 11) *1 | | | |
| | White Balance | AWC (2,000 - 10,000 K), ATW1 (2,700 - 6,000 K), ATW2 (2,000 - 6,000 K) | | | |
| | Maximum shutter | Max. 1/10000 s to Max. 16/30 s | | | |
| | Intelligent Auto | On / Off | | | |
| | Super Dynamic | On / Off, The level can be set in the range of 0 to 31. | | | |
| | Dynamic Range | Max. 102 dB (Super Dynamic : On, Level: 31) | | | |
| | Adaptive Black Stretch | — | | | |
| | Back light compensation / High light compensation | BLC (Back light compensation) / HLC (High light compensation) / Off (only when Super dynamic / Intelligent Auto : Off) | | | |
| | Fog compensation | On / Off, The level can be set in the range of 0 to 8. (only when Intelligent auto / auto contrast adjust: Off) | | | |
| | Maximum gain (AGC) | The level can be set in the range of 0 to 11. | | | |
| | Color/BW (ICR) | Off / On (R Light Off) / On (R Light On) / Auto1 (R Light Off) / Auto2 (R Light On) / Auto3 (SCC) | | | |
| | IR LED Light | High / Middle / Low / Off, Maximum irradiation distance : 20 m (Approx. 65 ft) | | | |
| | Digital Noise Reduction | The level can be set in the range of 0 to 255. | | | |
| | Video Motion Detection (VMD) | On / Off, 4 areas available | | | |
| | Scene Change Detection(SCD) | On / Off, 1 areas available | | | |
| | Privacy Zone | On / Off, Up to 8 zones available | | | |
| | Image rotation ² | 0° (Off) / 90° / 180° (Upside-down) / 270° | | | |
| | Camera Title (OSD) | On / Off, Up to 20 characters (alphanumeric characters, marks) | | | |
| | Lens | Focal length | 2.9 mm - 7.3 mm(1/8inches-9/32inches) | | |
| Zoom ratio | | 2.5x Optical zoom (Motorized zoom / Motorized focus) 3.3x FHD Extra Optical Zoom (when resolution is 1920x1080) | | | |
| Digital (electronic) zoom | | Choose from 3 levels of x1, x2, x4 | | | |
| Angular Field of View | | [16 : 9 mode] *[4:3 mode] is not supported. Horizontal : 44° (TELE) - 102° (WIDE) Vertical : 25° (TELE) - 57° (WIDE) | | | |
| Maximum Aperture Ratio | | 1 : 2.0 (WIDE) - 1 : 3.0 (TELE) | | | |
| Focus range | 1 m (39-3/8 inches) - ∞ | | | | |
| DORI | Detect (25ppm / 8ppf) | Wide: 41.5 m / 136.0 ft, Tele: 126.7 m / 415.8 ft | | | |
| | Observe (62.5ppm / 19ppf) | Wide: 16.6 m / 54.4 ft, Tele: 50.7 m / 166.3 ft | | | |
| | Recognize (125ppm / 38ppf) | Wide: 8.3 m / 27.2 ft, Tele: 25.3 m / 83.2 ft | | | |
| | Identify (250ppm / 76ppf) | Wide: 4.1 m / 13.6 ft, Tele: 12.7 m / 41.6 ft | | | |
| Adjusting Angle | | Horizontal (PAN) angle: ±180°, Vertical (TILT) angle: -30° - +85° Azimuth (YAW) angle: ±100° | | | |
| Browser GUI | Camera Control | Brightness | | | |
| | GUI / Setup Menu Language | English, Italian, French, German, Spanish, Portuguese, Russian, Chinese, Japanese | | | |
| Network | Network IF | 10Base-T / 100Base-TX, RJ45 connector | | | |
| | Resolution H.265/H.264 | [16:9 mode(2688x1520 30fps mode)], [16:9 mode(2688x1520 25fps mode)] 2688x1520, 1920x1080, 640x360, 320x180 [16:9 mode(30fps mode)], [16:9 mode(25fps mode)] 2560x1440, 1920x1080, 640x360, 320x180 *[4:3 mode] is not supported. | | | |
| | H.265/H.264 | Transmission Mode Transmission Type Max. frame rate for each stream ³ | | | |
| | | Unicast / Multicast | | | |
| | | | | | |
| JPEG | Image Quality | 10 steps | | | |

| | | | | |
|----------------------|------------------------------------|---|--|--|
| Network | Smart Coding | GOP(Group of pictures) control: On(Frame rate control) / On(Advanced) / On(Mid.) / On(Low) / Off *Frame rate control and Advanced are only available with H.265. AUTO VIQS: On / Off | | |
| | Audio Compression | — | | |
| | Audio transmission mode | — | | |
| | Supported Protocol | IPv6 : TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, SMTP, DNS, NTP, SNMPv1/v2/v3, DHCPv6, RTP, MLD, ICMP, ARP, IEEE 802.1X, DiffServ, MQTT ⁴ , LLDP ⁴ IPv4 : TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, RTSP, RTP, RTP/RTCP, SMTP, DHCP, DNS, DDNS, NTP, SNMPv1/v2/v3, UPnP, ICMP, ARP, IEEE 802.1X, DiffServ, MQTT ⁴ , LLDP ⁴ | | |
| | No. of Simultaneous Users | Up to 14 users (Depends on network conditions) | | |
| | SDXC/SDHC/SD Memory Card | H.265/H.264 recording: Manual REC / Alarm REC (Pre/Post) / Schedule REC Compatible SDXC/SDHC/SD Memory Card : microSDXC memory card: 64 GB, 128 GB, 256 GB, 512 GB microSDHC memory card: 4 GB, 8 GB, 16 GB, 32 GB microSD memory card: 2 GB | | |
| | Mobile Terminal Compatibility | iPad, iPhone, Android™ terminals | | |
| | ONVIF® Profile | G / S / T | | |
| | Alarm | Alarm Source | VMD alarm, SCD alarm, Command alarm | |
| | | Alarm Actions | SDXC/SDHC/SD memory recording, E-mail notification, HTTP alarm notification Indication on browser, TCP alarm notification output | |
| Input/ Output | Monitor Output (for adjustment) | — | | |
| | Audio input | — | | |
| | Audio Output | — | | |
| | External I/O Terminals | — | | |
| General | Safety | UL (UL60950-1), c-UL (CSA C22.2 No.60950-1), CE, IEC60950-1 | | |
| | EMC | FCC (Part15 ClassA), ICES003 ClassA, EN55032 ClassB, EN55024 | | |
| | Power Source and Power Consumption | PoE (IEEE802.3af compliant) Device : DC48 V 135 mA, Approx. 6.5 W (Class 0 device) | | |
| | Ambient Operating Temperature | -10 °C to +50 °C (+14 °F to +122 °F) {Power On range: 0 °C to +50 °C (+32°F to +122 °F)} | | |
| | Ambient Operating Humidity | 10 to 90 % (no condensation) | | |
| | Dimensions | ø129.5 mm x 101 mm (H) (ø5-3/32 inches x 3-31/32 inches (H)) Dome radius 40 mm (1-9/16 inches) | | |
| | Mass (approx.) | Approx. 350 g (0.77 lbs) | | |
| | Finish | Main body : ABS resin, I-PRO white Dome section : Acrylic resin, Clear | | |

*1 Converted value


*2 When "4:3(30fps mode)" or "4:3(25fps mode)" is selected for "Image capture mode", "90 °" and "270 °" cannot be selected.

*3 Smart Coding(GOP and AUTO VIQS) is not available when setting 30fps.

*4 It may be necessary to upgrade the firmware to use these protocols.









Appearance






Unit : mm (inches)



Optional Accessories

Mount Bracket / Other

| WALL | | POLE | CORNER |
|--|--|--|--|
| 1 | 2 | 1 | 1 |
| Wall Mount Bracket WV-QWL500-W (White)  | Wall Mount Bracket WV-QWL501-W (White)  | Pole Mount Bracket PAPM4W (White)  | Corner Mount Bracket PACA4W (White)  |
| Adapter Box WV-QJB500-W (White)  *If needed. | Mount Bracket WV-QSR501-W (White)  | Wall Mount Bracket WV-QWL500-W (White) (+ WV-QJB500-W)  | Wall Mount Bracket WV-QWL500-W (White) (+ WV-QJB500-W)  |

| HANGING | | CEILING | |
|---|---|---|---|
| 1 | 2 | 1 | 2 |
| Ceiling Mount Bracket WV-QCL501-W (White)  | Ceiling Mount Bracket WV-QCL101-W ^{*1} (White)  | Ceiling Mount Bracket WV-Q105A  | Ceiling Mount Bracket (Embedded) WV-QEM100-W (White)  |
| Mount Bracket WV-QSR501-W (White)  | This bracket requires 1 1/2" NPT pipe. | | |

*1 : It's possible to be used on the camera side and ceiling side. If used on both side, 2pieces are required.

Dome Cover



Trademarks and registered trademarks

- iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries.
- Android is a trademark of Google LLC.
- ONVIF is a trademark of ONVIF, Inc.
- All other trademarks identified herein are the property of their respective owners.

Important

- Safety Precautions : Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or other manufacturers' products used on the network.

• Masses and dimensions are approximate. • Specifications are subject to change without notice.